



SAFETY NON SLIP FLOOR COATING TRACTION SPRAY



- Slip resistant epoxy coatings
- Synthetic grit - No sharp edges
- Adheres to most surface types
- Durable - Wear and chemical resistant
- Indoor/outdoor - Not harmed by UV light
- Easy to use aerosol spray

DRYMIX TRACTION SPRAY is a skid-resistant epoxy-ester coating that provides a hard, flat, textured finish. DRYMIX TRACTION SPRAY is designed for interior and exterior use on wood, concrete, steel, fiberglass, aluminium and other surfaces where controlled footing is desired.

SURFACE PREPARATION: The surface should be dry, clean and free of oil, wax, dirt, loose paint and other contaminants. Previously painted surfaces should be washed with TSP (Trisodium Phosphate), rinsed and dried. Test a small area for compatibility and adhesion. If necessary, remove all the old paint down to the original surface. Recoating may be necessary depending on wear, each 3 to 6 months. DRYMIX TRACTION SPRAY is self-priming on most surfaces. Be sure first coat is dry before applying a second coat.

WOOD: Exterior wood surfaces should be sanded and primed with an exterior primer.

CONCRETE: Etch concrete, rinse and let dry. Apply DRYMIX TRACTION SPRAY direct - no primer needed.

FIBERGLASS: Sand lightly, then wash with soap and water or wipe with Acetone and white rag.

UNPAINTED ALUMINIUM: Clean using an aluminium metal etch. Rinse, let dry and apply DRYMIX TRACTION SPRAY direct.

DRY TIME: DRYMIX TRACTION SPRAY dries to touch and can be recoated in approximately one hour. The rate of cure will vary with the film thickness, temperature and humidity. Wait 24 hours or more before subjecting DRYMIX TRACTION SPRAY to heavy foot traffic. DRYMIX TRACTION SPRAY will continue to cure for several days.

DIRECTIONS FOR USE: For best results, spray with temperatures between 21 °C - 32 °C. Do not apply DRYMIX TRACTION SPRAY below 10 °C as the paint will not spray or dry properly. DRYMIX TRACTION SPRAY must be mixed well before use to achieve the correct color and texture. Shake can for 2 minutes. The ball will roll freely when completely mixed. Repeat shaking the can as needed during application. Hold the can 30-35cm from surface to be coated. Keep finger tip out of the spray pattern.

WARNING

FLAMMABLE AEROSOL. Do not spray near naked flame. Keep away from sources of ignition – No Smoking. Keep out of reach of children. Do not breathe spray. Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal. Use only in well ventilated areas.

STORAGE & DISPOSAL

Do not expose to heat, protect from sunlight and do not expose to temperatures exceeding 50 degrees. Do not puncture or incinerate even when empty.

FIRST AID

If swallowed, do not induce vomiting. Call Poisons information Centre (0800 764 766) or call a doctor. In case of eye contact, flush immediately with plenty of water and get medical attention; for skin, wash thoroughly with soap and water. If you experience breathing difficulties, leave the area to obtain fresh air, if problems continue seek medical attention.

PROPELLENT: Hydrocarbon



Made in USA

Distributed by:

Drymix NZ Ltd, PO Box 109, Greenhithe, Auckland 0756

Tel: 0800-DRYPHONE (379 746)

Fax: 0800-DRYMIX (379 649)

www.drymix.co.nz